


- a. Calcule a inércia da viga BC de modo a que a encurvadura no plano 1-3 se verifique para a carga  $P=1500 \text{ kN}$ .

Plano 1-3 = Plano da estrutura  $\Rightarrow I = I_2$



$$1500 = \frac{\pi^2 \times 210 \times 10^6 \times 348 \times 10^{-8}}{L_e^2} \Rightarrow L_e = 2,193 \Rightarrow L_e/L = 0,731$$

$h_1 = 1$  (apoio A)

$$0,731 = \left[ \frac{1 + 0,145(\eta_1 + \eta_2) - 0,265\eta_1\eta_2}{2 - 0,364(\eta_1 + \eta_2) - 0,247\eta_1\eta_2} \right] \Rightarrow h_2 = 0,156$$


$$\theta = \frac{L}{3EI} = \frac{1}{K}$$

$$0,156 = \frac{1}{1 + K \frac{3}{4 \times E \times 348 \times 10^{-8}}} \Rightarrow \frac{K}{E} \simeq 25,1 \times 10^{-6}$$

$$\frac{3EI}{L} = K = 25,1 \times 10^{-6} E \Rightarrow I = \frac{25,1 \times 10^{-6} \times 1,5}{3} \simeq 1255 \text{ cm}^4$$

b. Para a situação da alínea a), calcule a carga crítica da coluna.

$P_{\text{plano } 2-3} = P_{\text{plano}} \perp \text{estrutura}$



$$L_e = 0,7 L$$

$$P_{cn}^{\perp} = \frac{\pi^2 \times 210 \times 10^6 \times 449,33 \times 10^{-8}}{(0,7 \times 3)^2} = 2112 \text{ kN}$$

$$P_{cn} = \min(2112, 1500) = \underline{\underline{1500}} \text{ kN}$$